
F.A.P. RTE.	SECTION	С	TANDO	1	TOTAL	SHEET NO.
374	G-B-I-1		COOK		15	14
STA.		T0	STA.			
FEO. RO	AD DIST. NO.	ILLINOIS	FED.	AID	PROJECT	

CONTRACT NO. 60D59




DIAPHRAGM D1 54-Required

* Provide 15/16 "x 2" vertical slotted holes in angles for diaphragms in stage construction bay (West Side of Beam 5).

- 1) Two hardened washers shall be required over all oversize holes for diaphragms.

 2) All splice plates shall conform to the supplemental requirements for Notch Toughness Zone 2. (NTR) in accordance with the General Notes.
- 3) Structural steel for diaphragms, filler plates and connection angles shall be AASHTO M270 Grade 50W.
- 4) Structural steel for splice plates shall be AASHTO M270 Grade 50W.



	REVISIONS			
	NAME	DATE	i	
			1	
			1	
STV Incorporated				
Engineers/Architects/Planners/Construction Managers				
Engineers/Architects/Planners/Construction Managers 200 W. Mourroe Street, Suite 1650 Chicago, IL. 60606-5015 312753-0655, FAX 3127553-0661				
512555 5555, FAX 512555-0001			[

ILLINOIS DEPARTMENT OF TRANSPORTATION ILLINOIS ROUTE 21 MILWAUKEE AVE. OVER DES PLAINES RIVER F.A.P. ROUTE 374 SECTION G-B-I-1 COOK COUNTY, SN 016-6566

DIAPHRAGM/SPLICE DETAILS

DESIGN BY: BTO DRAWN BY: BTO DATE: 8/29/07 CHECKED BY: JAN CHECKED BY: JAN